

8" HD 24/7 Touch Monitor

Metal Housing - Anti-Glare - Anti-Fingerprint - 1200 cd/m²



Monitor Performance

- Rugged Metal Housing
- 1,200NIT sunlight-readable, 6S3P 50K-hr WLED backlight
- 1280x 720 High-Definition Resolution
- High-Performance color accuracy
- OSD with LED
- Operating temperature: -30°C ~ 85°

Enhanced Touch System Performance

- TRU-Flat Zero Bezel IP65 rated PCAP 10-Point Multi-Touch System compatible with fingers, capacitive styluses, and nitrile, latex, and vinyl gloves
- Optical bonding with AR & AF coatings
- USB HID-Compliant Plug & Play functionality with no calibration required (USB B-A & USB-C)
- Industry-Leading Touch Response: 5ms response time for seamless interaction

Specifications

Viewable Image Size	8" / 16:9
Native Resolution	HD 1280x 720 @ 60Hz
Contrast Ratio	1300:1
Brightness	1200 cd/m ²
Viewing Angle (MTBF)	178° Vert., 178° Hor. 50,000 Hours
Pixels Per Inch	84 @ native resolution
Response Time	(Tr/Tf) 20/5 ms
Input Connections	DP (MTS), HDMI (1.4) & USB-C (PD & CC protocol), 3.5mm
Audio IN/Out	
Internal Speakers	Built-in 5 watt speakers
Power	≤ 20W AC 100-240V 50/60Hz, DC 12V/5A
Dimensions (WxHxD)	
Stand NOT Included	
Net (without stand)	8.57in x 5.53in x 1.37 in.
Monitor Net Weight	2.3 lbs.
VESA Specification	75 x 75mm & AMPS
Warranty	3 Years